



SOUND BA C10-2R

GYPSUM PLASTERBOARD
DRYWALL CONSTRUCTION

Tech Specs

| | | | | |
|------------------------|------------|--------------------------------|---------------------|-------------------|
| Dimensional tolerances | | Type | SOUND BA C10-2R | |
| Thickness | +/- 0.5 mm | | DI | EN 520 |
| With | +0/-4 mm | Reaction to fire | A2-s1,d0 (B) EN 520 | |
| Length | +0/-5 mm | Thermal Conductivity λ | W/(m.°C) | 0.25 EN ISO 10456 |
| | | Density | kg/m ³ | ≥ 800 |
| Application | | Dimensions | | |
| wall linings | | Thickness | mm | 12.5 |
| | | width | mm | 1200 |
| | | Lengths | mm | 2400 |
| | | Nominal Weight. | | |
| | | Board Thick. 12.5 mm | kg/m ² | 9.4 |
| | | Breaking Loads EN 520 | | |
| | | Thickness | 12.5 mm | |
| | | Longitudinal | ≥550 | |
| | | Transversal | ≥210 | |
| | | Acoustic Viel | white | |
| | | Perforated area | 9% | |
| | | Perforated padron | | |
| | | | | |
| Ceilings | | Dimensions (mm) | | |
| | | | | |
| Partitions | | Tapered Edge - BA | | |
| | | | | |



To maintain GYPFOR SOUND BA C10-2R performance integrity, the drywall plasterboard should be protected from exposure to adverse conditions during storage and construction.