

AENOR

GESTÃO
DE QUALIDADE
ISO 9001



EUROGYPSUM



GYPSUM PLASTERBOARD
DRYWALL CONSTRUCTION



PLATINUM

Application

The GYPFOR PLATINUM plate is plasterboard is designed for interior drywall applications where an improved fire resistance, greater resistance to bending and impact are required. Suitable for applications in areas potentially exposed to impacts and high movement of people such as gyms, hotels or shopping centers.

Enhanced quality board designed for applications where extra moisture resistance is required, such as kitchens, bathrooms, laundries, public bathrooms in hospitals, hotels, and schools.

Suitable for:

- Suspended Ceilings
- Partition walls
- Existing wall linings

Physical Characteristics

Board Type

EN 520 D, F, H1, I, R

Core

Non-combustible, dimensionally stable, inert gypsum

Paper

100% recycled; colour copper

Longitudinal Edge

Tapered edge (TE)

Transversal Edge

Square edge (SE)

Label colour

Black

Gypsum plasterboard with water-repellent additives and fiberglass that improves its fire resistance and reduce its water absorption capacity. Gypsum board primer should be applied before painting or adding any textural material.




Technical specifications


Dimensional tolerances		Type	AQUA, FIRE, ACOUSTIC	
Thickness:	±0.5 mm	Reaction to fire	D, I, F, H1, R	EN 520
Width:	+0/-4 mm	Thermal conductivity	A2-s1,d0 (B)	EN 520
Length:	+0/-5 mm	Density	0.25	EN ISO 10456
		Specific heat	$W/(m \cdot ^\circ C)$	
		Water vapor resistance μ	kg/m^3	≥ 950
		Air permeability	$kJ/(kg \cdot ^\circ C)$	1
		Surface hardness		EN ISO 10456
		Total water absorption	$m^3/(m^2 \cdot S \cdot Pa)$	10
		Surface water absorption		EN ISO 10456
		Dimensions	mm	1.4 x 10 ⁶
		Thickness:	mm	< 15
		Width:	mm	< 5
		Length:	mm	≤ 180
		Approximate weight		EN 520
		Board thickness 12,5 mm	kg/m^2	1200
		Board thickness 15 mm	kg/m^2	2000, 2400, 2500
		Breaking loads		
		Thickness		12.5 15
		Longitudinal	N	≥ 725 ≥ 870
		Transverse	N	≥ 300 ≥ 360
		Edge		
		Tapered Edge - TE		

Application


Wall Linings



Ceilings



Partitions



This plasterboard has a non-combustible core and additives that improve its mechanical resistance to fire, making it suitable systems with special fire protection requirements. It also has a special waterproofing treatment for increased moisture resistance, however it is not indicated for application in direct contact with water, nor in environments of high permanent humidity. It can be coated with ceramics or similar materials.

Sizes (mm)

