

AENOR

GESTÃO
DE QUALIDADE
ISO 9001



EUROGYPSUM

**GYP
FOR**

GYPSUM PLASTERBOARD
DRYWALL CONSTRUCTION



AQUA

Application

The GYPFOR AQUA plasterboard is designed for use in interior wall and ceiling applications. Should not be used in applications where temperatures exceed 52 °C for extended periods, or in areas with extreme humidity.

Enhanced quality board designed for applications where extra moisture resistance is required, such as kitchens, bathrooms, laundries, public bathrooms in hospitals, hotels, and schools. Suitable for:

- Suspended Ceilings
- Partition walls
- Existing wall linings

Physical Characteristics

Board type
EN 520 H1

Core
Non-combustible, dimensionally stable, inert gypsum

Paper
100% recycled; colour green

Longitudinal Edge
Tapered edge (TE)

Transversal Edge
Square edge (TE)

Label colour
Black

Board with special waterproofing treatment for reduced water absorption. Gypsum board primer should be applied before painting or adding any textural material.




Technical Specifications

Dimensional tolerances


Thickness:	±0.5 mm
Width:	+0/-4 mm
Length:	+0/-5 mm

Application


Wall linings



Ceilings



Partitions



Type	AQUA		EN 520
	H1		
Reaction to fire	A2-s1, d0		EN 520
Thermal conductivity	$W/(m \cdot ^\circ C)$	0.25	EN ISO 10456
Density	kg/m^3	≥ 660	
Dimensions			
Thicknesses	mm	12.5	
Width	mm	900	
Lengths	mm	1800	
Approximate weight			
Board thickness 12.5 mm	kg/m^2	8.5	

Breaking loads

Thickness		12.5	
Longitudinal	N	≥550	
Transversal	N	≥210	

Edge

Tapered Edge - TE



This plate has a special waterproofing treatment for increased moisture resistance, however it is not indicated for application in direct contact with water, nor in environments of high permanent humidity. It can be coated with ceramics or similar materials.

Sizes (mm)

